

.... Sanimarin 32

EASY TO INSTALL AGAINST A VERTICAL PARTITION.



..... COMPACT AND COMFORTABLE

TECHNICAL FEATURES

Pumping height	3 m
Horizontal pumping distance	30 m
Non return valve	Integrated
Outlet diameter	38 mm or 25 mm
Supply voltage	12 V or 24 V DC
Motor power	300 W (12 V), 360 W (24 V)
Electricity consumption	Dependent upon the control system (see detail p.30)
Water consumption	Dependent upon the control system from 1.2 L to 2.4 L
Water use	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11 L/min
Weight	19 kg

REFERENCES

DESIGNATION	CODE	EAN
Sanimarin 32 Comfort 12 V	SN3212VLC	3308815076478
Sanimarin 32 Comfort 24 V	SN3224VLC	3308815076485
Sanimarin 32 Plus 12 V	SN3212VLCP	3308815076492
Sanimarin 32 Plus 24 V	SN3224VLCP	3308815076508
Sanimarin 32 Premium 12 V	SN3212VPREMIUM	3308815077888
Sanimarin 32 Premium 24 V	SN3224VPREMIUM	3308815078052
Sanimarin 32 Luxe 12 V	SN3212VCLAVSFA	3308815076515
Sanimarin 32 Luxe 24 V	SN3224VCLAVSFA	3308815076522

4 CONTROL SYSTEMS



Electric switch **Comfort**




Pneumatic button **Plus**



Electric button **Premium**



Electronic keyboard **Luxe**



Mounting on a raised step



All the system integrated in the foot



Vertical back line



Connection to the pressurised water onboard



Quiet



Soft close seat

TECHNICAL VIEWS



DIMENSIONS (MM)

